



MULTI-SPIKE

0
0
12
12



For general aeration, the standard 1/8" (3mm) thick triangular knife will give you 8" (200mm) deep slits at a close 6" (150mm) spacing, while the fine slitting drum will give you 4" (100mm) deep slits at an extra close 3" (75mm) spacing.

For maximum penetration, even in hard ground, we recommend the optional hydraulic weight system.

MULTI-SPIKE 1200

Deep penetration - Improves drainage and opens up the turf in both winter and summer programs

Fast operation - Covers large areas rapidly leaving a quality finish

5 optional types of knives - truckster, deep slitting, twist, fine slitting, coring spoon

Optional Wheel Kit- for tow-behind operation.

Weight options - hydraulic or static weights. Enables the user to obtain the most from his tractor and achieve maximum penetration



WORKING SPECIFICATIONS

| | |
|--|---|
| Working width | 56" (1,350 mm) |
| Working depth | Up to 10" (250 mm) |
| Weight | 880 lbs (400 Kg) |
| Hole spacing side-to-side | 3" (75 mm), with fine slit knives 6" (150 mm), with all other knives/tines |
| Hole spacing in drive direction, at maximum depth center-to-center | With 3 knives per disk: 18" (440 mm) With 4 knives per disk: 13" (330 mm) With 6 knives per disk: 9" (220 mm) With 12 knives per disk: 4 1/2" (110 mm) |
| Recommended minimum tractor size | 18 HP with lift capacity of minimum 1,100 lbs (500 Kg), or 12HP for towed version |
| Capacity: At 5 km/hour (3.1mph) At 10km/hour (6.2mph) At 15km/hour (9.4 mph) | 72,656 sq ft (6,750 sq m)/hour 145,313 sq ft (13,500 sq m)/hour 217,969 sq ft (20,250sq m)/hour |
| Shipping dimensions | 59" x 22" x 66" (1,480 mm x 550 mm x 1,640 mm) L x W x H |
| Three point linkage | 3- point CAT 1 & 2 |
| Lubrication grease | EP 2 |
| Standard items | Rear roller assembly Manual Support jack |
| Optional tine kits: | truckster knife, twist knife, deep knife, fine slit knife, coring spoon |

FEATURES / BENEFITS

| FEATURE | BENEFIT |
|-------------------------|--|
| Rear roller | Smooth and clean finish |
| Weight transfer options | Hydraulic system or static weights guarantee full penetration. |
| 2 optional prime movers | Tractors or trucksters. |
| Solid construction | For a long active life |

CALL FOR YOUR FREE DEMO TODAY!

Our commitment is to fully satisfy the needs of our customer. For immediate assistance, contact your local distributor or our Sales & Marketing Office at 636-326-1009.



Redexim North America Inc.
29 Cassens Court
Fenton, MO 63026, USA
Tel: 636-326-1009
Fax: 636-326-4884
www.redexim.com
E-mail: redexim@aol.com